

Heavy Series

SUMITOMO TIRE ST520

Premium Wide Base

More tread depth means more miles to removal. With 24/32nd", ST520 has 40% more usable tread depth than many competitors.

- Deeper tread depth for more traction and in-service time.
- Stone ejectors protect the casing from damage in the groove base.
- Application specific tread compound resists cutting and chipping.
- Four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.



Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5531990	385/65R22.5	18/J	11.75	12.25	120	9,370	-	-	42.5	14.9	-	24	19.7	484	65/105
5531993	425/65R22.5	20/L	12.25	13.00	125	11,400	-	-	44.5	16.6	-	24	20.4	473	65/105
5531996	445/65R22.5	20/L	13.00	14.00	120	12,300	-	-	45.6	17.8	-	24	20.8	464	65/105

SUMITOMO TIRE ST720

Value Wide Base

A durable all position wide base tire with a long - standing reputation for high mileage and vehicle stability.

- Wide shoulder ribs stabilize the vehicle in turns and at highway speeds.
- Application specific tread compound resists cutting and chipping.
- Four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.



Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5531490	385/65R22.5	18/J	11.75	-	120	9,370	-	-	42.2	14.9	-	18	19.4	502	65/105
5531493	425/65R22.5	20/L	13.00	-	120	11,400	-	-	44.2	16.5	-	19	20.4	478	65/105
5531496	445/65R22.5	20/L	14.00	13.00	120	12,300	-	-	45.3	17.6	-	20	20.7	470	65/105

SUMITOMO TIRE ST770

Free Rolling Wide Base

A wide-base tire specially designed for spread-axle trailer service.

- Notches in solid shoulder ribs reduce effects of scuffing in turns.
- Application specific tread compound resists cutting and chipping.
- Four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.



Product Code	Tire Size	Load Range Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max I.P. (psi)	Single Max Load (lbs)	Dual Max I.P. (psi)	Dual Max Load (lbs)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Skid Depth (x/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph/kmh)
5531590	385/65R22.5	18/J	11.75	-	120	9,370	-	-	42.2	14.8	-	18	19.5	498	65/105